Drives	GWP (green-house potential)	Ozone depletion potential	Acidifi-cation potential	Eutrophi-cation potential	Photo-chemical oxidation potential	Abiotic depletion - elements	Abiotic depletion - fossil	Primary energy not renewable	Primary energy renewable	Freshwater consump-tion
	(GWP 100)	(ODP)	(AP)	(EP)	(POCP)	($ADP_{el.}$)	(ADP_{fos})	($PE_{n\ reg}$)	(PE_{reg})	(H_2O)
	kg CO_2-equivalent	kg R11-equivalent	kg SO_2-equivalent	kg PO_4^{3-}	kg C_2H_4-equivalent	kg Sb-equivalent	MJ	MJ	MJ	m^3
KS2 S2 24	9,20E+00	4,27E-08	3,28E-02	2,50E-03	-2,68E-03	1,23E-03	5,40E+03	1,09E+02	4,03E+01	4,74E+01
KS2 S12 24	1,30E+01	6,05E-08	4,65E-02	3,53E-03	-3,80E-03	1,74E-03	7,65E+03	1,54E+02	5,71E+01	6,72E+01
KS2 TWIN	2,61E+01	1,21E-07	9,29E-02	7,07E-03	-7,59E-03	3,47E-03	1,53E+04	3,09E+02	1,14E+02	1,34E+02
KS2 Set	2,68E+01	1,25E-07	9,57E-02	7,28E-03	-7,82E-03	3,58E-03	1,57E+04	3,18E+02	1,18E+02	1,38E+02
KS2 230	2,30E+01	1,07E-07	8,20E-02	6,24E-03	-6,70E-03	3,06E-03	1,35E+04	2,73E+02	1,01E+02	1,19E+02
KSA 24	1,69E+01	7,83E-08	6,01E-02	4,57E-03	-4,91E-03	2,25E-03	9,90E+03	2,00E+02	7,39E+01	8,69E+01
KSA 230	3,53E+01	1,64E-07	1,26E-01	9,56E-03	-1,03E-02	4,70E-03	2,07E+04	4,18E+02	1,55E+02	1,82E+02
KSA TWIN/D	3,30E+01	1,53E-07	1,18E-01	8,94E-03	-9,60E-03	4,39E-03	1,93E+04	3,91E+02	1,44E+02	1,70E+02
KS15	6,90E+01	3,20E-07	2,46E-01	1,87E-02	-2,01E-02	9,19E-03	4,05E+04	8,18E+02	3,02E+02	3,56E+02
PLA6	1,15E+01	5,34E-08	4,10E-02	3,12E-03	-3,35E-03	1,53E-03	6,75E+03	1,36E+02	5,04E+01	5,93E+01
PLA8	1,84E+01	8,54E-08	6,56E-02	4,99E-03	-5,36E-03	2,45E-03	1,08E+04	2,18E+02	8,06E+01	9,48E+01
PLA101	1,46E+01	6,76E-08	5,19E-02	3,95E-03	-4,24E-03	1,94E-03	8,55E+03	1,73E+02	6,38E+01	7,51E+01
PLA116	1,84E+01	8,54E-08	6,56E-02	4,99E-03	-5,36E-03	2,45E-03	1,08E+04	2,18E+02	8,06E+01	9,48E+01
PLA10	3,45E+01	1,60E-07	1,23E-01	9,36E-03	-1,01E-02	4,60E-03	2,02E+04	4,09E+02	1,51E+02	1,78E+02
PLA16	3,45E+01	1,60E-07	1,23E-01	9,36E-03	-1,01E-02	4,60E-03	2,02E+04	4,09E+02	1,51E+02	1,78E+02
PLS15	5,52E+01	2,56E-07	1,97E-01	1,50E-02	-1,61E-02	7,35E-03	3,24E+04	6,54E+02	2,42E+02	2,84E+02
PLS30	6,98E+01	3,24E-07	2,49E-01	1,89E-02	-2,03E-02	9,30E-03	4,09E+04	8,27E+02	3,06E+02	3,60E+02
PLS50	5,52E+01	2,56E-07	1,97E-01	1,50E-02	-1,61E-02	7,35E-03	3,24E+04	6,54E+02	2,42E+02	2,84E+02
SP8 24	1,53E+01	7,12E-08	5,47E-02	4,16E-03	-4,47E-03	2,04E-03	9,00E+03	1,82E+02	6,72E+01	7,90E+01
SP8 230	3,83E+00	1,78E-08	1,37E-02	1,04E-03	-1,12E-03	5,11E-04	2,25E+03	4,54E+01	1,68E+01	1,98E+01
LKS (-T)	1,15E+01	5,34E-08	4,10E-02	3,12E-03	-3,35E-03	1,53E-03	6,75E+03	1,36E+02	5,04E+01	5,93E+01
LKS-TV	2,30E+01	1,07E-07	8,20E-02	6,24E-03	-6,70E-03	3,06E-03	1,35E+04	2,73E+02	1,01E+02	1,19E+02
FTA R	1,84E+01	8,54E-08	6,56E-02	4,99E-03	-5,36E-03	2,45E-03	1,08E+04	2,18E+02	8,06E+01	9,48E+01
LLA10	1,15E+01	5,34E-08	4,10E-02	3,12E-03	-3,35E-03	1,53E-03	6,75E+03	1,36E+02	5,04E+01	5,93E+01
LLA16	1,69E+01	7,83E-08	6,01E-02	4,57E-03	-4,91E-03	2,25E-03	9,90E+03	2,00E+02	7,39E+01	8,69E+01
FVUx	1,15E+01	5,34E-08	4,10E-02	3,12E-03	-3,35E-03	1,53E-03	6,75E+03	1,36E+02	5,04E+01	5,93E+01
OFV	1,46E+01	6,76E-08	5,19E-02	3,95E-03	-4,24E-03	1,94E-03	8,55E+03	1,73E+02	6,38E+01	7,51E+01
FV	1,53E+01	7,12E-08	5,47E-02	4,16E-03	-4,47E-03	2,04E-03	9,00E+03	1,82E+02	6,72E+01	7,90E+01
PL6 / PL10	1,15E+01	1,89E-06	1,18E+02	1,07E+01	7,52E+00	1,64E-02	1,43E+02	1,36E+02	3,56E+01	5,93E+01

Declaration code: **M-EPD-AZR-101**
Programme operator: **ift Rosenheim GmbH**
Theodor-Gietl-Str. 7-9,
83026 Rosenheim, Germany
LCA prepared by: **Life Cycle Engineering Experts**
Berliner Allee 58,
64295 Darmstadt, Germany
Declaration holder: **Aumüller Aumatic** GmbH.

The declaration is based on the PCR (Product Category Rules) document „Building Components for Smoke and Heat Control Systems" No. PCR-RW-1.1:2013.

LCA calculations were based on the „cradle to grave" life cycle including all upstream processes (e.g. raw material extraction, etc.).

The reference service life has been specified to 25 years. The calculation of the life cycle scenarios is based on a service life of **50 years** per electrical device.

The life cycle was modelled using the sustainability software tool „GaBi6" for the development of Life Cycle Assessments. For the consideration of the impact categories the characterisation factors of the ELCD (European Reference Life Cycle Database) were used.

In accordance with the REACH candidate list, no substances of very high concern are contained.